

Home Solutions Centralized Wastewater Treatment Microscreening / Filtration Filtration of biolog. treated wastewater

HUBER Solutions for Filtration of Biologically Treated Wastewater



Filtration of biologically treated wastewater serves for removal of suspended solids (suspensa) remaining in clarifier effluents. Such suspensa contain about 50 % carbon, almost 10 % nitrogen and over 1 % phosphorus.

Around 1 mg/L (ppm) of phosphorus remain in the effluent, even if the biological treatment stage is designed for enhanced biological phosphorus removal and/or chemical phosphorus precipitation. Subsequent filtration is necessary where stringent phosphorus limits must be reliably maintained.

- Our rotary mesh screen HUBER Disc Filter RoDisc® is provided with fabric of a mesh size between 0.01 and 0.1 mm. The fabric is applied on both sides of slowly rotating discs.
- Wastewater flows continuously upstream through our HUBER Sandfilter CONTIFLOW®, and its sand bed is continuously backwashed.
- Membrane Bio-Reactors perform biological treatment and filtration. Our Membrane Filters retain not only all solids but also all bacteria within the bio-reactor.

19 Apr 2024 22:30:59

Huber Technology (Pty) Ltd

Company Reg. No.: 1992/006606/07

PO Box 9813 George, 6530 South Africa

Phone +27 44 874 4242 Fax +27 44 874 3658 huber@lantic.net http://www.hubersa.com

A member of the HUBER Group